

AMENDMENTS

In the Claims

1. (Currently Amended) An adaptable storage unit for dispensing containers in a selectively cascading first-in, first-out manner, the storage unit comprising:
 - a receiving area configured to receive containers;
 - a user-accessible dispensing area configured to provide containers;
 - a storage track configured to convey containers from the receiving area to the dispensing area; and
 - a selectively engageable stop positioned proximate the user-accessible dispensing area, the selectively engageable stop configured to hold containers at the dispensing area for access by a user if the selectively engageable stop is engaged.
2. (Original) The unit of claim 1, wherein the selectively engageable stop is further configured to pass containers from the dispensing area to another storage unit if the selectively engageable stop is disengaged.
3. (Original) The unit of claim 1, wherein the selectively engageable stop is further configured to redirect containers from the dispensing area to a storage track of a cascaded storage unit.
4. (Original) The unit of claim 1, wherein the receiving area and the dispensing area are arranged such that the dispensing area of a first stacked storage unit substantially overlaps with the receiving area of a second stacked storage unit.

5. (Original) The unit of claim 1, wherein the storage track is configured to convey specific containers selected from the group consisting of barrels, bottles, boxes, cans, cartons, casks, crates, drums, jars, kegs, packages, sacks, tins, and tubs.
6. (Original) The storage unit of claim 1, wherein the storage track comprises a receptor track member configured to convey containers from the receiving area and a provider track member configured to convey containers to the dispensing area.
7. (Original) The storage unit of claim 6, further comprising a redirection member configured to redirect containers from the receptor track member to the provider track member.
8. (Original) The storage unit of claim 6, wherein at least one of the track members is nearly horizontal.
9. (Original) The storage unit of claim 6, wherein at least one of the track members is selected from the group consisting of a shelf, a conveyer belt, and rollers.
10. (Original) The storage unit of claim 6, wherein at least one of the track members comprises at least one fillet.
11. (Original) The storage unit of claim 1, wherein the selectively engageable stop comprises a member selected from the group consisting of a slat, a panel, a pin, and a latch.
12. (Original) The storage unit of claim 1, wherein the selectively engageable stop is removable.

13. (Original) The storage unit of claim 1, wherein the selectively engageable stop is pivotally attached to the storage track.

14. (Original) The storage unit of claim 1, wherein the selectively engageable stop is electronically actuated.

15. (Original) The storage unit of claim 1, wherein the selectively engageable stop further comprises a spring.

16. (Original) The storage unit of claim 1, wherein the selectively engageable stop is counter balanced.

17. (Original) The storage unit of claim 1, further comprising at least one track height adjustment member configured to adjust the height of the storage track.

18. (Original) The storage unit of claim 17, wherein the at least one track height adjustment member is further configured to hold the storage track in an inclined position.

19. (Currently Amended) A method for dispensing containers in a selectively cascading first-in, first-out manner, comprising:

receiving a container on a storage track; and

holding the container at a user-accessible dispensing area to prevent the container from passing to another storage unit vertically aligned with the storage track if a selectively engageable stop is engaged, wherein the user-accessible dispensing area and the selectively engageable stop are proximate one another.

20. (Original) The method of claim 19, further comprising passing the container to another storage unit vertically aligned with the storage track if a selectively engageable stop is disengaged.

21. (Original) The method of claim 19, wherein selectively engaging a stop further comprises electronically engaging the stop.

22. (Original) The method of claim 19, wherein placing a container on the storage track comprises using a mechanical device to place a container on a track.

23. (Currently Amended) An adaptable storage unit for dispensing containers in a selectively cascading first-in, first-out manner, the storage unit comprising:

means for conveying containers to a redirection member;

means for conveying containers from the redirection member to a user-accessible dispensing area; and

means for selectively passing containers from the user-accessible dispensing area to another storage unit, wherein the means for selectively passing containers is proximate to the user accessible dispensing area.